



Surface Pack™ Box

Siemon's Surface Pack Box is best described as a compact, lightweight box often utilized in high density work area environments that require rapid deployment of cabling systems. Typically deployed in buildings with a raised floor system, environments range from call centers to trading floors.


The box supports rapid deployment by allowing connectivity to be pre-terminated and stored away while construction is finalized. Cables can be routed within flexible conduit (not supplied), secured to the box and terminated to outlets. The small overall footprint allows the box and connectivity to be stored under a raised floor and then passed through standard size floor grommets for efficient deployment to the work station.

Surface Pack Boxes are available in 3 port and 6 port versions. Both boxes are the same size and compatible with MAX®, Z-MAX® and TERA® outlets allowing customers to support Category 5e, 6, 6A and 7A installations. The outlets are presented at an angle to allow patch cords to dress less prominently off the face of the box. Blanks may be used to accommodate port count variants and allow for expansion in the future. Ample labeling is provided for both the box and ports.

Two mounting options are available. One method features a mounting bracket that can be secured to a fixed location and allows the box to be clipped into the bracket via a one touch latch. For additional security, the box can be mounted without the use of the bracket by securing the base directly to the work area surface.



Pre-mountable Bracket — Allows box to be quickly installed at the work area location



Cable Tie Down Point — Within box secures cables for proper strain relief



Easy Access — All terminations and cables are contained within the box cover allowing easy access to terminations

Product Information

PERFORMANCE SPECIFICATIONS

Mechanical Properties		
	3 Port	6 Port
Part Number	SP-3-01	SP-6-01
Conduit Opening	26 mm (1 in.)	32 mm (1.25 in.)
Dimensions		
Length	192 mm (7.5 in.)	
Width	54 mm (2 in.)	
Height	61 mm (2.4 in.)	
Weight	181 grams (6.3 oz.)	
Material	Polycarb / ABS	
Flammability Rating	UL 94 V-0	
Operating Temperature	-10° C to +60° C (14° F to 140° F)	
Relative Humidity	Up to 95%, non-condensing	
Storage Temperature	-40° C to +70° C (14° F to 158° F)	
Outlet Compatibility	TERA®, Z-MAX® Hybrid UTP or Shielded, MAX® Flat UTP Outlets, MAX Blanks	
Color	Black	

Ordering Information

Part #	Description
SP-3-01	3 Port Surface Pack™ Box, Black
SP-6-01	6 Port Surface Pack Box, Black



SP-3-01



SP-6-01

Box Includes:

- 3 - Port identification labels and covers
- 1 - Box label and cover
- 1 - (203mm) Tie-wrap
- 1 - Screw for securing cover to the base of the box

For related product information request Spec Sheet(s):

MAX® outlets, Z-MAX® outlets, TERA® Outlets

Z-MAX, MAX, and TERA are trademarks of The Siemon Company.

Because we continuously improve our products, Siemon reserves the right to change specifications and availability without prior notice.

For additional resource information:

Visit our web site at www.siemon.com

Worldwide Headquarters North America

Watertown, CT USA
Phone (1) 860 945 4200 US
Phone (1) 888 425 6165

Regional Headquarters EMEA

Europe/Middle East/Africa
Surrey, England
Phone (44) 0 1932 571771

Regional Headquarters Asia/Pacific

Shanghai, P.R. China
Phone (86) 21 5385 0303

Regional Headquarters Latin America

Bogota, Colombia
Phone (571) 657 1950